

Yacht Wax

General Product Description

Product description	Solvent-free wax emulsifier for the preservation of GFK and painted surfaces. Protects from salt water and premature ageing through oxidation.
Areas of application	Gel-coat and painted surfaces on hulls, superstructures etc.
Constituents	Carnauba wax, citric acid, cellulose, water, vegetable-based emulsifier
Colour:	Transparent. Milky when liquid, yet clear when dry.
Storage:	Keep tightly sealed and out of the reach of children. Store in cool but frost-free conditions.
Shelf-life	minimum of 2 years if tin is kept firmly sealed
Can sizes:	1 l
Class of risks	

Technical Data

Consumption	5 – 30 ml/m ² per coat
Drying time	Can be polished after 15 minutes at 20° C room temperature is and average humidity.

How to use

Surface requirements	The surface must be dry and free of dust and grease.
Application	Evenly apply thin layer with cloth or sponge. Only use if temperature is above 10°C. Stir well before use. Leave to dry and polish with cloth, soft buffer cover etc.
Note	The advice contained on this technical data sheet is the result of years of research and practical application. It is for information only and does not constitute a performance guarantee. Customers are advised to test the suitability of all products for their area of application. The manufacturer reserves all rights to change the mixture of this product for reasons of technological and ecological progress.